



12v 17ah lead acid battery

12v 17ah lead acid battery

All product and company names are trademarks or registered trademarks of their respective holders. Use of such names/marks by UPS Battery Center does not imply any affiliation with or endorsement by their respective owners. Use of third party part or model numbers are solely for identification purposes only. UPS Battery Center is in no way implying that any of its products are original equipment manufacturer replacement batteries. Specifications are subject to change without notice.

- Absorbent Glass Mat (AGM) technology for efficient gas recombination of up to 99% and freedom from electrolyte maintenance or water adding
- Not restricted for air transport-complies with IATA/ICAO Special Provision A67
- UL-recognized component
- Can be mounted in any orientation
- Computer designed lead, calcium tin alloy grid for high power density
- Long service life in float or cyclic applications
- Maintenance-free operation
- Low self discharge

- UPS Standby Power Applications
- Data Centers
- Emergency 911 Centers
- Hospitals & Medical Applications
- Military Power Equipment
- Emergency Lighting
- Fire Detection and Alarm Devices

Product Specifications Dimensions Terminal Type: F3 Length (mm/inch): 181/7.13 Width (mm/inch): 77/3.03 Height (mm/inch): 167/6.57 Total Height (mm/inch): 167/6.57 Approx. Weight (kg/lbs): 5.1/11.2

Operating Temperature Range Discharge: -15°C ~ 50°C (5°F ~ 122°F) Charge: -10°C ~ 50°C (14°F ~ 122°F) Storage: -20°C ~ 50°C (-4°F ~ 122°F)

Constant Power Discharge Characteristics (Note) The above characteristics data are average values obtained within three charge/discharge cycles not the minimum values.



12v 17ah lead acid battery

Contact us for free full report

Web: <https://hollanddutchtours.nl/contact-us/>

Email: energystorage2000@gmail.com

WhatsApp: 8613816583346

