

Desoutter air tools catalogue

Established in 1914, Desoutter has since grown to become a world leader in electric assembly solutions. For over a century, this remarkable journey has been fueled by continuous innovation. Today, Desoutter stands as a globally recognized name, not only for their pioneering work in pneumatic screwdrivers and drills, but also for their cutting-edge tightening systems, drilling solutions, and assembly software.

Assembly Tools - Selection Guide TOOL TYPE BATTERY TOOLS ELECTRIC NUTRUNERS ELECTRIC TRANSDUCERIZED EB TOOLS - PC & Networks/Software - CVI3 ELECTRIC TRANSDUCERIZED EB TOOLS - PC & Networks/Software - CVIR II / MULTICVIL II / CVIL II ELECTRIC CURRENT CONTROLLED EB TOOLS - CVIC / POSCO ELECTRIC FASTENING TOOLS PNEUMATIC FASTENING TOOLS TORQUE MEASUREMENT SYSTEMS - Software CUSTOMIZED SOLUTIONS: Screwfeeders - Multiplus - Arms

E-LIT Series - Optimize your performance Clutch Battery Tool range Focus Clear feedback Ergonomic handle High accuracy clutch Lithium-ion battery Brushless motor 45°; oriented battery 2 positions 3 MODELS TO CHOOSE FROM LI-ION BATTERY SPEED MODULE E-LIT PLUS Electronic brushless (ELB) Pistol and Angle E-LIT premium Electronic brushless speed control (ELS) Pistol and Angle E-LIT Wireless Communication with E-LIT Box (ELC) Pistol and Angle

Speed setting For ELS and ELC models Two speed setting easily controlled by external module Everything needed to optimize your assembly process Guarantee quality and keep high productivity • ecrease final speed to ensure D tightening quality • void quality defects in your final product A • ecrease starting speed to facilitate bolt engagement D

E-LIT BOX For Poka-Yoke Application Focus Wireless communication WIRELESS SYSTEM Maintenance alert Safe report Fast to connect Wireless visual feedback EASY PAIRING PROCESS 1- Trigg input 1 and 2 (by PLC or simulator) 2- Power on the BOX 3- Press both, tool trigger and reverse, while inserting battery pack 4- Pairing completed

E-LIT Series 0.4 to 45 Nm (3.5 to 398 in.lb) - 50 to 1550 rpm PART NUMBER TORQUE RANGE ROTATIONAL SPEED E-lit plus - electronic brushless motor A A A A A E-lit premium - Electronic brushless speed setting E-lit wireless - communication with E-LIT BOX Battery not included in standard offering WEIGHT WITHOUT BATTERY

B-FLEX Series 5 to 95 Nm (3.7 to 70 ft.lb) - 10 to 900 rpm SQUARE DRIVE B-FLEX - Transducerized battery tool TORQUE RANGE MAX. MIN. RECOMMENDED ROTATIONAL SPEED WEIGHT WITHOUT BATTERY

Contact us for free full report

Web: <https://hollanddutchtours.nl/contact-us/>

Email: energystorage2000@gmail.com

WhatsApp: 8613816583346

